



ETN ISY-STEEL n° A.25.09618 (02/04/26)
Modules validés – validated modules

								Pressure limit Long side (Pa)		Pressure limit Short side (Pa)	
Manufacturer	Module reference	Peak power min max		Length mm	Width mm	Thick. mm	Weight kg	Front	Back	Front	Back
Aiko	AIKO-Axxx-MCE54Dw (Neostar 3P+54)	465	495	1762	1134	30	20,6	2400	5400	1600	2400
	AIKO-Axxx-MCE54Mw (Neostar 3P54)	470	500	1762	1134	30	20,6	2400	5400	1600	2400
	AIKO-Axxx-MCE54Db (Neostar 3S+54)	460	475	1762	1134	30	20,6	2400	5400	1600	2400
	AIKO-Axxx-MCE54Mb (Neostar 3S54)	460	475	1762	1134	30	20,6	2400	5400	1600	2400
	AIKO-Axxx-MCE54Mb (Neostar Pro 3S54)	480	490	1762	1134	30	20,6	2400	5400	1600	2400
DMEGC	DMxxxG12RT-B48HST/HBT/HSW/HBW/HBB	450	475	1762	1134	30	24	2400	5400	1600	1800
	DMxxxG12RT-G48HSW/HBW	455	475	1762	1134	30	24	2400	5400	1600	1800
	DMxxxG12RT-B54HST/HBT/HSW/HBW/HBB	500	525	1961	1134	30	27	2400	5400	1600	1800
	DMxxxM10RT-B60HBT	490	510	1950	1134	30	26,8	2400	5400	1200	1600
	DMxxxM10RT-54HSW-L/HBW-L/HBB-L/HSW-LV/HBW-LV/HBB-LV	445	465	1762	1134	30	15	2400	5400	N/A	N/A
DualSun	FLASH - DSxxx-108M10RTB-03	425	450	1762	1134	30	24,5	3600	6600	1600	2400
	FLASH - DSxxx-96M10RTB-07	450	460	1762	1134	30	24,6	3600	6600	1600	2400
	FLASH - DSxxx-108M10RTB-07	500	515	1960	1134	30	27,3	2400	5400	1600	2400
	FLASH - DSxxx-144M10T-03	600	600	2278	1134	30	26,6	2400	5400	1600	2400
JA Solar	JAM54D40-xxx/LB (1,6 mm)	430	460	1762	1134	30	22	2400	5400	1600	1600
	JAM54D40-xxx/LB (2,0 mm)	435	460	1762	1134	30	24,8	2400	5400	1600	1600
	JAM60D41-xxx/LB	485	510	1953	1134	30	27,3	2400	5400	N/A	N/A
	JAM66D42-xxx/MB	570	595	2278	1134	30	31,8	2400	5400	N/A	N/A
LONGi	LR7-54HVB-xxxM	475	500	1800	1134	30	21,6	2400	5400	2000	2400
	LR7-54HVD-xxxM	475	500	1800	1134	30	23,5	2400	5400	2000	2400
	LR7-54HVB-xxxM (Explorer)	475	490	1800	1134	30	21,6	2400	5400	2000	2400
	LR7-60HVD-xxxM	520	555	1990	1134	30	28	2400	5400	1100	1800
	LR7-60HVHL-xxxM	535	560	1990	1134	30	16,3	2400	3600	N/A	N/A





ETN ISY-STEEL n° A.25.09618 (02/04/26)
Modules validés – validated modules

Manufacturer	Module reference	Peak power min max		Length mm	Width mm	Thick. mm	Weight kg	Pressure limit Long side (Pa)		Pressure limit Short side (Pa)	
								Front	Back	Front	Back
Tongwei	TWMNH-48HD	420	475	1762	1134	30	24,0	2400	5400	1600	1600
	TWMNH-48HE	425	475	1762	1134	30	23,7	2400	5400	1600	1600
	TWMNH-48HW	425	475	1762	1134	30	20,9	2400	5400	1600	1600
	TWMNH-54HD	475	535	1961	1134	30	26,5	2400	5400	1600	1600
Trina Solar	TSM-xxxNEG18R.25	485	510	1961	1134	30	24	2400	5400	1000	2400
	TSM-xxxNEG18R.28	475	505	1961	1134	30	23,5	2400	5400	1000	2400
	TSM-xxxNEG18RC.27	485	505	1961	1134	30	24	2400	5400	1000	2400
	TSM-xxxNEG9R.28	430	475	1762	1134	30	21	4000	5400	1600	2200
Voltec Solar	TARKA 110 VSMP	425	460	1868	1070	35	21	3000	6000	1800	2400
	TARKA 110 VSBP	425	460	1868	1070	35	21	3000	6000	1800	2400
	TARKA 120 VSMP	475	500	1868	1170	35	22,8	2400	5400	1600	2100
	TARKA 120 VSBP	475	500	1868	1170	35	22,8	2400	5400	1600	2100

Service client – Customer service
+33.6.65.40.09.17 | contact@isy-pv.com
Support Technique – Technical support
+33.6.65.65.88.86 | technique@isy-pv.com



SAS ISY-PV - 20 AVENUE DU PIC DE BERTAGNE - 13420 - GEMENOS
Capital 100 000 € - RCS Marseille B - SIRET 928 271 220 00016 - FR 29 928 271 220